

PRODUCTS & SERVICES YOU CAN RELY ON



WWW.GULFAMERICA.COM

YOUR TRUSTED PARTNER IN WIRE ROPE SOLUTIONS

At Gulf America Wire Rope, we deliver equipment and services that exceed expectations in quality and reliability. Our commitment is built on three core principles:

- **Safety First:** Ensuring the highest standards in every product and service.
- **Exceptional Customer Service:** Founded on trust and dependability.
- **Technical Expertise:** Supported by outstanding service every step of the way.

Our team carefully documents, tests, and certifies each product to ensure top-tier quality at every stage. We treat every project as an opportunity to build lasting relationships, creating tailored solutions that exceed expectations.

When high-performance slings are required, Gulf America Wire Rope delivers. We adhere to rigorous safety standards, using premium components for maximum safety and reliability, backed by exceptional customer support.

Rely on Gulf America Wire Rope for the quality and performance you deserve.

PRODUCTS AND SERVICES

FABRICATED ASSEMBLIES

- Alloy Chain Slings for Overhead Lift
- Breakout Lines
- Cable Laid Slings
- Drag Lines
- Drill Lines
- Grommets: Cable Laid and Rope Laid
- Mechanical Spliced Single-Leg and Multi-leg Bridle Slings
- Multi-Part Braided Wire Rope Slings
- Nylon Web Slings
Single-Ply; 2-Ply; 3-Ply; 4-Ply & Endless
- Polyester Round Slings
- Spelter Socketing: Resin
- Swage Socketing
- Swing & Escape Ropes
- Tie-down Assembles (for trucking industry)
- Winch Lines

RIGGING HARDWARE

- Alloy Chain & Chain Fittings
- Alloy Shackles
- Bolt Type Shackles
- Chain Falls
- Clevis Grab Hooks
- Clips
- Crane Blocks & Sheaves
- Eye Hoist Hooks
- Lever Type Chain Hoists
- McKissick Snatch Blocks
- Nylon Web Sling Saver Shackles
- Overhaul Balls
- Ratchet Type Load Binders
- Screw pin Shackles
- Shur-loc Hooks
- Sling Choker Hooks
- Spelter Sockets
- Swage Sockets
- Swivels
- Swivel Eye Hooks
- Turnbuckles
- Wire Rope Come-Along
- Wedge Sockets

INSPECTION OF SLINGS

INSPECTION FREQUENCY PER ASME B30.9

A VISUAL INSPECTION FOR DAMAGE SHALL BE PERFORMED BY THE USER OR DESIGNATED PERSON EACH DAY OR SHIFT THE SLING IS USED. A COMPLETE INSPECTION FOR DAMAGE SHALL BE PERFORMED PERIODICALLY BY A DESIGNATED PERSON, AT LEAST ANNUALLY. WRITTEN RECORDS OF MOST RECENT PERIODIC INSPECTION SHALL BE MAINTAINED.

REJECTION CRITERIA PER ASME B30.9

MISSING OR ILLEGIBLE SLING IDENTIFICATION; EVIDENCE OF HEAT DAMAGE; SLINGS THAT ARE KNOTTED; FITTINGS THAT ARE PITTED, CORRODED, CRACKED, BENT, TWISTED, GOUGED, OR BROKEN; OTHER CONDITIONS, INCLUDING VISIBLE DAMAGE, THAT CAUSE DOUBT AS TO THE CONTINUED USE OF THE SLING.

WIRE ROPE SLINGS	CHAIN SLINGS	WEB SLINGS	ROUND SLINGS
EXCESSIVE BROKEN WIRES, FOR STRAND-LAID AND SINGLE PART SLINGS, TEN RANDOMLY DISTRIBUTED BROKEN WIRES IN ONE ROPE LAY OR FIVE BROKEN WIRES IN ONE STRAND IN ONE ROPE LAY	CRACKS OR BREAKS EXCESSIVE WEAR, NICKS OR GOUGES	ACID OR CAUSTIC BURNS MELTING OR CHARRING OF ANY PART OF THE SLING	ACID OR CAUSTIC BURNS EVIDENCE OF HEAT DAMAGE
SEVERE LOCALIZED ABRASION OR SCRAPPING, KINKING, CRUSHING, BIRDCAGING	STRETCHED CHAIN LINKS OR COMPONENTS	HOLES, TEARS, CUTS OR SNAGS	HOLES, TEARS, CUTS, ABRASIVE WEAR OR SNAGS THAT EXPOSE THE CORE YARNS
ANY OTHER DAMAGE RESULTING IN DAMAGE TO THE ROPE STRUCTURE	BENT, TWISTED OR DEFORMED CHAIN LINKS OR COMPONENTS	BROKEN OR WORN STITCHING IN LOAD BEARING SPLICES	BROKEN OR DAMAGED CORE YARNS
SEVERE CORROSION OF THE ROPE OR END ATTACHMENTS	EXCESSIVE PITTING OR CORROSION	EXCESSIVE ABRASIVE WEAR	WELD SPLATTER THAT EXPOSES CORE YARNS
	LACK OF ABILITY OF CHAIN OR COMPONENTS TO HINGE FREELY	DISCOLORATION AND BRITTLE OR STIFF AREAS ON ANY PART OF THE SLING, WHICH MAY MEAN CHEMICAL OR ULTRAVIOLET / SUNLIGHT DAMAGE	DISCOLORATION AND BRITTLE OR STIFF AREAS ON ANY PART OF THE SLINGS, WHICH MAY MEAN CHEMICAL OR OTHER DAMAGE
	WELD SPLATTER		

NDE INSPECTION/LOAD TESTING DIVISION

NDE INSPECTION SERVICES

ALL INSPECTIONS ARE PERFORMED IN ACCORDANCE WITH AWS D1.1, D1.2, DNV, AND ASME STANDARDS AND BY CERTIFIED LEVEL 2 INSPECTORS WORKS WITH ALL THIRD PARTY MONITORS SUCH AS DNV, ABS, LLYODS REGISTRY, ETC.

CAN HELP WITH SUPPLYING ENGINEERING/FABRICATION SERVICES

TEST PERFORMED

MT (MAGNETIC PARTICLE; VISIBLE AND FLUORESCENT)

PT (LIQUID PENETRANT)

VT (VISUAL TESTING)

LOAD TESTING

GA FACILITY TEST STAND (BROUSSARD LA)

150K VERTICAL TEST STAND AT GA YARD

DNV DROP TESTING

MOBILE/LOCATION TESTING

FULL INTEGRITY LOAD TESTING TRUCK PULLS UP TO 100K

FULL INTEGRITY TEST TRAILER PULLS UP TO 50K




SINGLE PADEYE PULLING; PULLS UP TO 30K PER PADEYE



WIRE ROPE AND CHAIN SLING RATINGS





SINGLE LEG SLING LOAD RATINGS

6 X 19 IWRC EXTRA IMPROVED PLOW STEEL (EIPS)
RATED CAPACITY IN TONS





ROPE DIA. (IN)	VERTICAL	CHOKER	VERTICAL BASKET
	 EIPS	 EIPS	 EIPS
1/4"	0.65	0.48	1.3
5/16"	1.0	0.74	2.0
3/8"	1.4	1.1	2.9
7/16"	1.9	1.4	3.9
1/2"	2.5	1.9	5.1
9/16"	3.2	2.4	6.4
5/8"	3.9	2.9	7.8
3/4"	5.6	4.1	11
7/8"	7.6	5.6	15
1"	9.8	7.2	20
1-1/8"	12	9	24
1-1/4"	15	11	30
1-3/8"	18	13	36
1-1/2"	21	16	42
1-5/8"	24	18	49
1-3/4"	28	21	57
2"	37	28	73
2-1/8"	40	31	80
2-1/4"	44	35	89
2-3/8"	49	38	99
2-1/2"	54	42	109
2-5/8"	60	46	119
2-3/4"	65	51	130
2-7/8"	71	55	141
3"	77	60	153
3-1/8"	82	64	165
3-1/4"	89	69	177
3-3/8"	95	74	190
3-1/2"	102	79	203

DOUBLE LEG SLING LOAD RATINGS




6 X 19 IWRC EXTRA IMPROVED PLOW STEEL (EIPS)
RATED CAPACITY IN TONS

ROPE DIA. (IN)	VERTICAL	60 DEGREES 60°	45 DEGREES 45°	30 DEGREES 30°
	 EIPS	 EIPS	 EIPS	 EIPS
1/4"	1.300	1.100	0.910	0.65
5/16"	2.0	1.7	1.4	1
3/8"	2.9	2.5	2.0	1.4
7/16"	3.9	3.4	2.7	1.9
1/2"	5.1	4.4	3.6	2.5
9/16"	6.4	5.5	4.5	3.2
5/8"	7.8	6.8	5.5	3.9
3/4"	11	9.7	7.9	5.6
7/8"	15	13	11	7.6
1"	20	17	14	9.8
1-1/8"	24	21	17	12
1-1/4"	30	26	21	15
1-3/8"	36	31	25	18
1-1/2"	42	37	30	21
1-5/8"	49	42	35	24
1-3/4"	57	49	40	28
2"	73	63	52	37

FOUR LEG SLING LOAD RATINGS

ROPE DIA. (IN)	VERTICAL	60 DEGREES 60°	45 DEGREES 45°	30 DEGREES 30°
	 EIPS	 EIPS	 EIPS	 EIPS
1/4"	2.6	2.2	1.8	1.3
5/16"	4.0	3.5	2.8	2.0
3/8"	5.7	5.0	4.1	2.9
7/16"	7.8	6.7	5.5	3.9
1/2"	10	8.8	7.1	5.1
9/16"	13	11	9	6.4
5/8"	16	14	11	7.8
3/4"	22	19	16	11
7/8"	30	26	21	15
1"	39	34	28	20
1-1/8"	48	42	34	24
1-1/4"	59	51	42	30
1-3/8"	71	62	50	36
1-1/2"	84	73	60	42
1-5/8"	98	85	69	49
1-3/4"	113	98	80	57
2"	147	127	104	73

CHAIN SLING RATINGS (GRADE 100 CHAIN) RATED CAPACITY IN POUNDS

CHAIN SIZE (INCHES)	 SINGLE LEG	 DOUBLE LEG CHAIN SLING				 FOUR LEG CHAIN SLING			
	VERTICAL	60 DEGREES	45 DEGREES	30 DEGREES	60 DEGREES	45 DEGREES	30 DEGREES		
1/4" (9/32")	4,300	7,400	6,100	4,300	11,200	9,100	6,400		
5/16"	5,700	9,900	8,100	5,700	14,800	12,100	8,500		
3/8"	8,800	15,200	12,400	8,800	22,900	18,700	13,200		
1/2"	15,000	26,000	21,200	15,000	39,000	31,800	22,500		
5/8"	22,600	39,100	32,000	22,600	58,700	47,900	33,900		
3/4"	35,300	61,100	49,900	35,300	91,700	74,900	52,950		
7/8"	42,700	74,000	60,400	42,700	110,900	90,600	64,000		
1"	59,700	103,400	84,400	59,700	155,100	126,400	89,550		
1-1/4"	90,400	156,600	127,800	90,400	234,900	191,700	135,600		

SYNTHETIC NYLON SLINGS

EYE AND EYE SLING



Sling made with flat loop eye on each end with loop eye opening on same plane as sling body. This type of sling is sometimes called a flat eye-and-eye or double-eye sling.

TWISTED EYE SLING



Sling made with both loop eyes formed except that the loop eyes are turned to form a loop eye which is at a right angle to the plane of the sling body.

ENDLESS SLING



Endless sling, sometimes referred to as a grommet. It is a continuous loop formed by joining the ends of the webbing together.






RATED CAPACITY FOR SYNTHETIC NYLON SLINGS IN POUNDS

PLY	PART NO	WIDTH	VERTICAL	CHOKER	BASKET
1	EEF-1-901	1"	1,600	1,280	3,200
1	EEF-1-902	2"	3,100	2,480	6,200
1	EEF-1-903	3"	4,700	3,760	9,400
1	EEF-1-904	4"	6,200	4,960	12,400
1	EEF-1-906	6"	9,300	7,440	18,600
1	EEF-1-908	8"	11,800	9,440	23,600
1	EEF-1-910	10"	14,700	11,760	29,400
1	EEF-1-912	12"	17,600	14,080	35,200
2	EEF-2-901	1"	3,100	2,480	6,200
2	EEF-2-902	2"	6,400	5,000	12,800
2	EEF-2-903	3"	8,800	7,040	17,600
2	EEF-2-904	4"	11,000	8,800	22,000
2	EEF-2-906	6"	16,500	13,200	33,000
2	EEF-2-908	8"	22,700	18,160	45,400
2	EEF-2-910	10"	28,400	22,720	56,800
2	EEF-2-912	12"	34,100	27,280	68,200
3	EEF-3-901	1"	4,300	3,440	8,600
3	EEF-3-902	2"	8,600	6,880	17,200
3	EEF-3-903	3"	12,600	10,080	25,200
3	EEF-3-904	4"	15,300	12,240	30,600
3	EEF-3-906	6"	23,550	18,840	47,100
3	EEF-3-908	8"	31,830	25,464	63,660
3	EEF-3-910	10"	38,200	30,560	76,400
3	EEF-3-912	12"	43,930	35,144	87,860
4	EEF-4-901	1"	5,500	4,400	11,000
4	EEF-4-902	2"	11,000	8,800	22,000
4	EEF-4-903	3"	16,400	13,120	32,800
4	EEF-4-904	4"	20,400	16,320	40,800
4	EEF-4-906	6"	30,960	24,480	61,200
4	EEF-4-908	8"	40,960	32,768	81,920
4	EEF-4-910	10"	48,000	38,400	96,000
4	EEF-4-912	12"	53,760	43,008	107,520

POLYESTER ROUND SLINGS



DESCRIPTION		RATED CAPACITY IN LBS.		
		VERTICAL	CHOKER	BASKET
PART NUMBER	CODE COLOR			
BRS 30	PURPLE	2,600	2,100	5,200
BRS 60	GREEN	5,300	4,200	10,600
BRS 90	YELLOW	8,400	6,700	16,800
BRS 120	TAN	10,600	8,500	21,200
BRS 150	RED	13,200	10,600	26,400
BRS 180	WHITE	16,800	13,400	33,600
BRS 240	BLUE	21,200	17,000	42,400
BRS 300	ORANGE	25,000	20,000	50,000
BRS 360	GREY	31,000	24,800	62,000
BRS 400	ORANGE	40,000	32,000	80,000
BRS 600	BROWN	53,000	42,400	106,000
BRS 800	OLIVE	66,000	52,800	132,000
BRS 1000	BLACK	90,000	72,000	180,000

PRODUCTS & SERVICES YOU CAN RELY ON

711 S. Martin Luther King Hwy.
Lake Charles, LA 70601



337.433.2216
lcsales@gulfamerica.com

CUSTOM HOSE ASSEMBLIES, FITTINGS, AND ACCESSORIES



ULTRA HIGH PRESSURE HOSE AND FITTINGS

Ultra high pressure hoses, valves, fittings, and tubing. Steel multi spiral reinforced hose up to 55,000 PSI working pressures with all accessories.



HYDRAULIC HOSE

Custom built hydraulic assemblies for any and every industry application.



INDUSTRIAL HOSE & COUPLINGS

All industrial hose applications for every industry including chemical, tank truck, oil, fuel, water, waste water, air, blast, ducting, heater hose, fuel, FDA food grade and dredge sleeve.



FLEXIBLE METAL HOSE & EXPANSION JOINTS

CUSTOM BUILT
Extreme temperatures, high pressures, harsh chemicals, mission critical.



PVC HOSES

Liquid manure, septic, wastewater, water suction, general oilfield applications, gas, diesel and biofuels



AIR HOSE

General purpose air, push-on, blast hose, and bull hose



Over 80 Years Combined Experience In The Custom Hose Fabrication Industry

WWW.GULFAMERICA.COM

PRODUCTS & SERVICES YOU CAN RELY ON

711 S. Martin Luther King Hwy.
Lake Charles, LA 70601



337.433.2216
lcsales@gulfamerica.com

CUSTOM HOSE ASSEMBLIES, FITTINGS, AND ACCESSORIES



PVC AQUA

Heavy duty suction and discharge hose perfect for pumping equipment, slides easy with visible flow confirmation



ULTRA HIGH PRESSURE ACCESSORIES

Valves, fittings, and tools up to 55,000 PSI.



INDUSTRIAL FITTINGS

Camlocks, hammer unions, kc nipples, and any industrial fitting for any applications.



FITTINGS

Hydraulic, pneumatic, instrumentation fittings, adapters and accessories. Stainless steel crimps, reusable fittings, valves and push on fittings.



HEAVY DUTY HOSE PROTECTION

Velcro wrap, sleeves, guards, straps, hose buns, plugs, grips, and pads.



VALVES

Ball valves, butterfly valves, foot valves, check valves, swing valves, and many more to any industry needs.

SRM INDUSTRIES INC.



Over 80 Years Combined Experience In The Custom Hose Fabrication Industry

WWW.GULFAMERICA.COM

PRODUCTS & SERVICES YOU CAN RELY ON

1047 Q.C.P. Park Drive
Broussard, LA 70518



337.364.2525
hose@gulfamerica.com

CERTIFIED LINCOLN DEALER




935 CFM COMPRESSOR

Make: Doosan / I.R.
Cubic Feet per Minute: (CFM) 935
Pounds per Square Inch: (PSI) 120
Length: 160" Width: 88" Height: 96"
Weight: 13500 LBS
** Fire-loop system installed * Rig Air system installed*



400/500 AMP WELDING MACHINE

Make: Lincoln
Sent with: 100' Lead, 50' Ground
10' Whip & Remote Rheostat
Length: 96" Width: 33"
Height: 62"
Weight: 3000 LBS



WIRE FEED WELDER (SUITCASE WELDER)

Make: Lincoln.
Includes: 10' Whip, 100' Gas Hose & Argon Gauge
** wire not included*



375 CFM COMPRESSOR

Make: Doosan / I.R.
Cubic Feet per Minute: (CFM) 375
Pounds per Square Inch: (PSI) 120
Length: 112" Width: 64"
Height: 78"
Weight: 6500 LBS



185 CFM COMPRESSOR

Make: Doosan / I.R.
Cubic Feet per Minute: (CFM) 185
Pounds per Square Inch: (PSI) 120
Length: 112" Width: 64"
Height: 77"
Weight: 4000 LBS



3000-3500 PSI DIESEL PRESSURE WASHER

Make: Gulf Tek
Sent With: 50' Hose, Wand, & 4 Tips
Weight: 500 LBS
** air start pressure washers available*



AIR TUGGERS / HOISTS

1K TUGGER:	2K TUGGER:
Weight: 90 LBS	Weight: 750 LBS
Cable: 5/16"x150'	Cable: 1/2"x200'
Min. CFM: 100	Min. CFM: 150

4K TUGGER:	10K TUGGER:
Weight: 1500 LBS	Weight: 2200 LBS



535 ELECTRIC PIPE THREADER

Make: Rigid (Offshore Skid)
Threads: 1/2" up to 2" Pipe
Dies and Cutting Oil Available
Nipple Chuck Available
Length: 44" Width: 34"
Height: 58 1/2"
Weight: 500 LBS



BOTTLE RACKS

2x10 Bottle Racks
Gas, Oxygen & Acetylene Available Upon Request
Tare: 3,000 LBS
Max: 5,000 LBS



MANIFOLDS / VOLUME TANKS

(20 Gal, 80 Gal, 120 Gal, 200 Gal, 240 Gal)
All Tanks are Fitted with 1" & 2"
Crows Feet.
Weight: 500-800 LBS

PRODUCTS & SERVICES YOU CAN RELY ON

1047 Q.C.P. Park Drive | Broussard, LA 70518 | 337.364.2525 | rentals@gulfamerica.com



AIR SAWS

Hack Saw w/clamp
Band Saw

Tig Saw

Reciprocating Saw

**blades are available upon request*



AIR IMPACT WRENCHES

Make: Ingersoll Rand

Sizes Include:

1/2" 3/4" 1"

**socket sets available upon request*



AIR SPIDERS

Cable: 5/16" x 100'

Available Items:

Transfer Chain

Beam Clamp

Cable Insulator

60' Yoyo's (Lanyards)



SCAFFOLDING & WALK BOARDS

5' x 5' scaffolding

Walkboards:

7' Boards

12' Boards

20' Boards

24' Boards

32 Boards

**available items: base plates & casters*



MAG DRILLS

Variable-speed, multiple-gear models

Reversible motors for tapping and machining

Swivel base stand for hard-to-reach areas

**air & electric*



RIVET BUSTER

Jumbo Rivet Buster with 11" Stroke

Bore Diameter: 1 3/156"

Blows per minute (BPM): 850

Operates at a minimum 90psi

**Bits (Flat & Point) are available upon request*

Weight: 33 LBS

Length: 25 1/2"



RIDGID 700 POWER PONY THREADER

Electric Hand-Held Threader with complete die set

** Pipe cutter accessory available*



GAS DETECTOR

HONEYWELL CERTIFIED

Simple one button operation for remote sampling in confined spaces

Units simultaneously monitor and display up to four potential atmospheric hazards

Measures O2, Combustibles/LEL, CO and H2S

Offer in-house calibrations, repairs, and sales

MISCELLANEOUS ITEMS

- 1" x 50' Air Hoses
- 2" x 25' Bull Hoses
- Air Chippers / Needle Scalers
- Hydraulic Hole Punch
- Cutting Rig
- Air Horn
- Squirrel Cage Blower
- Multi Vane Air Drill
- 20lbs Chipping Hammers
- 3/4" & 1" Torque Wrenches
- 250 Gallon Offshore Water Tote
- Personnel Baskets



4000 WATT 8KW DIESEL LIGHT TOWER

3 Cylinder

120/240 Voltage

2200 LBS

WWW.GULFAMERICA.COM